


Thermal Paper Specifications


F065-02

ITEM			UNIT	65g/m ²	NOTE
Base Weight			g/m ²	65±5%	ISO 536
Caliper			μm	72±5%	ISO 534
Brightness			% ISO	≥81	ISO 2470
Moisture			%	6.5±1	ISO 287
Smoothness(Bekk)			S	≥250	ISO 5627
Roughness			μm	≤2.0	ISO 8791
Tensile Strength		MD	kgf/15mm	≥3.2	ISO 1924
Tearing Strength		CD	gf	≥25	ISO 1974
Barcode Readable			Grade	A	Zebra105SL
Image Property	Dynamic Image	0.28mj/dot	O.D	≥0.90	TH-M2/N
		0.42mj/dot	O.D	≥1.18	
	Static Image	70℃	O.D	≤0.20	SWT
		105℃	O.D	≥1.05	
Durability	Humidity Resistance	Back ground	O.D	≤0.20	40℃ • 90%RH • 24h
		Printed part	O.D	≥0.90	
	Humidity Resistance	Back ground	O.D	≤0.20	60℃ • 90%RH • 24h
		Printed part	O.D	≥0.90	
	Heat Resistance	Back ground	O.D	≤0.20	60℃dry • 24h
		Printed part	O.D	≥0.75	
	Light Resistance	Back ground	O.D	≤0.20	SUNTEST • 1h
		Printed part	O.D	≥0.90	

DYNAMIC SENSITIVITY



STATIC SENSITIVITY



Gold Hua Sheng Paper(Suzhou Industrial Park)Co.Ltd.
 No.2 Jinsheng Road, Shengpu, Suzhou,Industrial Park,
 Tel:+86-512-62836666 Fax:+86-512-62832076
 800Toll-free hot-line: +86-8008282009
 Website:http://www.goldhs.com.cn

